

Page 1 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

GB

Seal-it® 217 EPDM Siliconen

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture: Silicone sealant Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

Connect Products B. V. Duurzaamheidsring 220 4231 EX Meerkerk Tel: +31 (0)347 341 916 http://conectproducts.nl

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (ISA) +1 872 5888271 (ISA)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP) The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains 2-Octyl-2H-isothiazol-3-one. May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %). The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).



Page 2 of 18

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

5.2 MIALORES	
O,O',O''-(methylsilylidyne)trioxime-2-pentanone	
Registration number (REACH)	01-2120004323-76-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	484-460-1
CAS	
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Acute Tox. 4, H302
factors	Eye Irrit. 2, H319

2-Octyl-2H-isothiazol-3-one	
Registration number (REACH)	
Index	613-112-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	247-761-7
CAS	26530-20-1
content %	0,00015-<0,0015
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH071
factors	Acute Tox. 2, H330
	Acute Tox. 3, H301
	Acute Tox. 3, H311
	Skin Corr. 1, H314
	Eye Dam. 1, H318
	Skin Sens. 1A, H317
	Aquatic Acute 1, H400 (M=100)
	Aquatic Chronic 1, H410 (M=100)
Specific Concentration Limits and ATE	Skin Sens. 1A, H317: >=0,0015 %
	ATE (oral): 125 mg/kg
	ATE (dermal): 311 mg/kg
	ATE (as inhalation, Mist): 0,27 mg/l/4h

Impurities, test data and additional information may have been taken into account in classifying and labelling the product. For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion



Page 3 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

GB

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire. Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon Silicon dioxide Hydrocarbons Toxic gases Formaldehyde Silicon dioxide Methanol Aldehydes Ethanol

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Or:

Pick up mechanically and dispose of according to Section 13.



Page 4 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

Allow product to harden. 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes. Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells. Store product closed and only in original packing. Store at room temperature. Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Silica, amorphous	3				Content %:
WEL-TWA: 6 mg/m3 (total inh.	dust), 2,4 mg/m3	WEL-STEL:				
(resp. dust)						
Monitoring procedures:	-					
BMGV:				Other information:		
Chemical Name	Calcium carbonat	e				Content %:
WEL-TWA: 4 mg/m3 (respirable (total inhalable dust)	e dust), 10 mg/m3	WEL-STEL:				
Monitoring procedures:		-				
BMGV:	-			Other information:		
-						
Chemical Name	Methanol					Content %:
WEL-TWA: 200 ppm (266 mg/n	n3) (WEL), 200	WEL-STEL:	250 ppm (333 r	ng/m3 (WEL)		
ppm (260 mg/m3) (EU)						
Monitoring procedures:			ol 25/a Methanol			
			119 SA (549 640))		
			119 U (549 657)			
				nittelgemische 6), DF		
	- 2	2013, 2002 - EL	J project BC/CEN	J/ENTR/000/2002-16	card 65-1	(2004)
	- N	NOSH 2000 (M	ETHANOL) - 199	98		
	- N	NOSH 2549 (V	OLATILE ORGA	NIC COMPOUNDS (SCREENI	NG)) - 1996
	Ν	NOSH 3800 (O	RGANIC AND IN	IORGANIC GASES E	BY EXTRA	CTIVE FTIR
	- 5	SPECTROMET	RY) - 2016			
	- [Draeger - Alcoh	ol 100/a (CH 29	701)		
BMGV:			·	Other information:	Sk (WEL	, EU)

@__



Page 5 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

Area of application	ne)trioxime-2-pentanone	Effect on health	Descripto	Value	Unit	Note
Area of application	Exposure route /	Effect on health	Descripto	value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	0,1	mg/l	
	Environment - marine		PNEC	0,01	mg/l	
	Environment - sediment,		PNEC	0,269	mg/kg	
	freshwater					
	Environment - sediment,		PNEC	0.057	mg/kg	
	marine					
	Environment - sewage		PNEC	2,15	mg/l	
	treatment plant			,	U U	
Consumer	Human - oral	Long term, systemic	DNEL	0.033	mg/kg	
		effects		,	bw/d	
Consumer	Human - inhalation	Long term, systemic	DNEL	0.057	mg/m3	
		effects		,	Ŭ	
Consumer	Human - dermal	Long term, systemic	DNEL	0,033	mg/kg	
		effects			bw/d	
Workers / employees	Human - inhalation	Long term, systemic	DNEL	0,2292	mg/m3	
		effects				
Workers / employees	Human - dermal	Long term, systemic	DNEL	0.065	mg/kg	
		effects		· ·	bw/d	

Silica, amorphous								
Area of application	Exposure route / Environmental compartment	Environmental		Value	Unit	Note		
	Environment - oral (animal feed)		PNEC	60000	mg/kg feed			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3			

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment - sediment, freshwater		PNEC	570,4	mg/kg	
	Environment - sediment, marine		PNEC	57,04	mg/kg	
	Environment - soil		PNEC	23,5	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	1540	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - inhalation	Long term, local effects	DNEL	26	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	26	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	4	mg/kg body weight/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	26	mg/m3	

@B-



Page 6 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

GB

Consumer	Human - oral	Short term, systemic effects	DNEL	4	mg/kg body weight/day
Consumer	Human - dermal	Long term, systemic effects	DNEL	4	mg/kg body weight/day
Consumer	Human - inhalation	Long term, systemic effects	DNEL	26	mg/m3
Consumer	Human - oral	Long term, systemic effects	DNEL	4	mg/kg body weight/day
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	20	mg/kg body weight/day
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	130	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	130	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	20	mg/kg body weight/day
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	130	mg/m3
Workers / employees	Human - inhalation	Long term, local effects	DNEL	130	mg/m3

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: With danger of contact with eyes.



GB Page 7 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen Tight fitting protective goggles with side protection (EN 166). Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). If applicable Protective gloves made of butyl (EN ISO 374). Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,5 Permeation time (penetration time) in minutes: 240 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended. Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments). Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown Observe wearing time limitations for respiratory protection equipment. Thermal hazards: Not applicable Additional information on hand protection - No tests have been performed. In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications. Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer. In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed. 8.2.3 Environmental exposure controls No information available at present. **SECTION 9: Physical and chemical properties** 9.1 Information on basic physical and chemical properties

Physical state:	Paste, solid.
Colour:	According to specification
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	Does not apply to solids.
Upper explosion limit:	Does not apply to solids.
Flash point:	Does not apply to solids.
Auto-ignition temperature:	Does not apply to solids.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	There is no information available on this parameter.
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,22 g/cm3
Relative vapour density:	Does not apply to solids.
Particle characteristics:	There is no information available on this parameter.
Particle characteristics:	There is no information available on this parameter.



Page 8 of 18

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

9.2 Other information

Explosives: Oxidizing solids: Product is not explosive. No

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling. 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7. Strong heat Moisture

10.5 Incompatible materials

See also section 7. Avoid contact with strong oxidizing agents. Avoid contact with other chemicals.

10.6 Hazardous decomposition products

See also section 5.2 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Seal-it® 217 EPDM Siliconen						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

O,O',O''-(methylsilylidyne)trioxime-2-pentanone							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	1234	mg/kg	Rat	OECD 425 (Acute		
					Oral Toxicity - Up-and-		
					Down Procedure)		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant	
					Dermal		
					Irritation/Corrosion)		



Page 9 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Irritant
damage/imation.					Irritation/Corrosion)	
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEL	200	mg/kg bw/d	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT- RE):	NOAEL	17	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Develop m. Tox. Screening Test)	

2-Octyl-2H-isothiazol-3-one						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	125	mg/kg			
Acute toxicity, by dermal	ATE	311	mg/kg			
route:						
Acute toxicity, by inhalation:	ATE	0,27	mg/l/4h			Dust, Mist
Symptoms:						ataxia,
						diarrhoea

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		References
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References,
• • •						Maximum
						achievable
						concentration.
Skin corrosion/irritation:				Rabbit		Not irritant,
						References
Serious eye				Rabbit		Not irritant,
damage/irritation:						Mechanical
						irritation
						possible.,
						References
Respiratory or skin				Guinea pig		Not sensitizising
sensitisation:						
Germ cell mutagenicity:						Negative
Carcinogenicity:						No indications
						of such an
						effect.
Reproductive toxicity						No indications
(Developmental toxicity):						of such an
						effect.
Symptoms:						eyes, reddened

œ-



Page 10 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute	
• • •					Oral toxicity - Fixe	
					Dose Procedure)	
Acute toxicity, by oral route:	LD50	> 5000	mg/kg	Rat		
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Not irritant,
damage/irritation:					Eye	Mechanical
					Irritation/Corrosion)	irritation
						possible.
Respiratory or skin						No (skin
sensitisation:						contact)
Germ cell mutagenicity:					in vitro	Negative
Carcinogenicity:						Negative,
						administered
						as Ca-lactate
Reproductive toxicity:						Negative,
-						administered
						as Ca-
						carbonate

Methanol	1	1		1		1
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	300	mg/kg	Human being		Experiences on
						persons.
Acute toxicity, by dermal	LD50	17100	mg/kg	Rabbit		Does not
route:						conform with
						EU
						classification.
Acute toxicity, by inhalation:	LC50	85	mg/l/4h	Rat		Not relevant for
						classification.,
						Vapours
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation	
					Test)	
Germ cell mutagenicity:				Mouse	OECD 474	Negative
					(Mammalian	
					Erythrocyte	
					Micronucleus Test)	
Carcinogenicity:				Mouse	OECD 453	Negative
					(Combined Chronic	
					Toxicity/Carcinogenicit	
					y Studies)	
Reproductive toxicity:	NOAEL	1,3	mg/l	Mouse	OECD 416 (Two-	
					generation	
					Reproduction Toxicity	
					Study)	
Specific target organ toxicity -	NOAEL	0,13	mg/l	Rat	OECD 453	
repeated exposure (STOT-					(Combined Chronic	
RE):					Toxicity/Carcinogenicit	
					y Studies)	

œ-



Page 11 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

Symptoms:			abdominal
Cymptonio.			
			pain, vomiting,
			headaches,
			gastrointestinal
			disturbances,
			drowsiness,
			visual
			disturbances,
			watering eyes,
			nausea, mental
			confusion,
			intoxication,
			dizziness

11.2. Information on other hazards

œ

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-
							elimination
							degree(complex
							ing organic
							substance)>=
							80%/28d: n.a.
Other information:							According to
							the recipe,
							contains no
							AOX.



Page 12 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and		28d	1	%		OECD 301 B	Not readily
degradability:						(Ready	biodegradable
						Biodegradability -	-
						Co2 Evolution	
						Test)	
12.3. Bioaccumulative	Log Pow		1,25			OECD 117	
potential:						(Partition	
						Coefficient (n-	
						octanol/water) -	
						HPLC method)	
12.1. Toxicity to fish:	LC50	96h	>113	mg/l	Oncorhynchus	OECD 203	
,					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	96h	113	mg/l	Oncorhynchus	OECD 203	
					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	NOEC/NOEL	48h	>=100	mg/l	Daphnia magna	OECD 202	
daphnia:					_	(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to	EC50	48h	>100	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	88	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	32	mg/l	Pseudokirchnerie	OECD 201	
				-	lla subcapitata	(Alga, Growth	
						Inhibition Test)	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,047	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	NOEC/NOEL	35d	0,0085	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,003	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,32	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErC10	48h	0,00022 4	mg/l	Navicula pelliculosa	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	0,00129	mg/l	Navicula pelliculosa	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			25	%		,	Not readily biodegradable
Toxicity to bacteria:	EC50		30,2	mg/l	activated sludge		¥

@-



Page 13 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

Toxicity to bacteria:	EC20	3h	7,3	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium
						Oxidation))

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>10000	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability: 12.3. Bioaccumulative							Abiotically degradable. Not to be
potential:							expected
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substanc

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:					Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Negative
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Not relevant for inorganic substances.

œ-



Page 14 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

œ

12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>200	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	15400	mg/l	Lepomis macrochirus		EPA-660/3-75- 009
12.1. Toxicity to daphnia:	EC50	96h	18260	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	96h	22000	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	99	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		28400		Chlorella vulgaris	,	Not to be expected
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	Log Pow		-0,77				
Other information:	DOC		<70	%			
Other information:	BOD		>60	%			

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts EC disposal code no.:



Page 15 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 07 02 17 waste containing silicones other than those mentioned in 07 02 16 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09 Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. suitable incineration plant. Hardened product: Can be disposed of with household rubbish. **For contaminated packing material**

For contaminated packing material

GB

Pay attention to local and national official regulations. Empty container completely. Uncontaminated packaging can be recycled. Dispose of packaging that cannot be cleaned in the same manner as the substance. 15 01 02 plastic packaging

SECTION 14: Transport information

General statements	
14.1. UN number or ID number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! General hygiene measures for the handling of chemicals are applicable.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2010/75/EU (VOC):

2,8 %

Treated goods as per Regulation (EU) No. 528/2012 must display specific information on the label.



Page 16 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

Please note Article 58 paragraph (3) subparagraph 2 of Regulation (EU) No. 528/2012. Approval of the biocidal active substance may mean that special conditions are required for marketing the treated goods. These are indicated in the approval of the active substance.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

GB

15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H330 Fatal if inhaled. H317 May cause an allergic skin reaction.

H317 May cause an allergic skin reaction.
H314 Causes severe skin burns and eye damage.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
EUH071 Corrosive to the respiratory tract.

Acute Tox. — Acute toxicity - oral Eye Irrit. — Eye irritation Acute Tox. — Acute toxicity - inhalation Acute Tox. — Acute toxicity - dermal Skin Corr. — Skin corrosion Eye Dam. — Serious eye damage Skin Sens. — Skin sensitization Aquatic Acute — Hazardous to the aquatic environment - acute Aquatic Chronic — Hazardous to the aquatic environment - chronic

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended. Guidelines for the preparation of safety data sheets as amended (ECHA). Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA). Safety data sheets for the constituent substances. ECHA Homepage - Information about chemicals. GESTIS Substance Database (Germany). German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended. National Lists of Occupational Exposure Limits for each country as amended. Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds



(GB) Page 17 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BSEF The International Bromine Council bw body weight Chemical Abstracts Service CAS Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of CLP substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dry weight dw for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances ΕN **European Norms** United States Environmental Protection Agency (United States of America) EPA $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera **European Union** EU EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general aen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc Kow octanol-water partition coefficient IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLIDInternational Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available NIOSHNational Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) persistent, bioaccumulative and toxic PBT . Polyethylene ΡE



Page 18 of 18 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 08.02.2022 / 0003 Replacing version dated / version: 01.11.2021 / 0002 Valid from: 08.02.2022 PDF print date: 08.02.2022 Seal-it® 217 EPDM Siliconen

PNEC Predicted No Effect Concentration ppm parts per million PVC Polyvinylchloride REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds vPvB very persistent and very bioaccumulative wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

GB

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.