

Page 1 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 08.02.2022 / 0011
Replacing version dated / version: 01.11.2021 / 0010
Valid from: 08.02.2022
PDF print date: 08.02.2022
Seal-it® 315 Facade-LM

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Seal-it® 315 Facade-LM

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Seam sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Connect Products B. V.
Duurzaamheidsring 220
4231 EX Meerkerk
Tel: +31 (0)347 341 916
<http://connectproducts.nl>

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (ISA)
+1 872 5888271 (ISA)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Trimethoxyvinylsilane. May produce an allergic reaction.
EUH210-Safety data sheet available on request.
EUH212-Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

(GB)

Page 2 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

| | |
|--|-------------------------------|
| Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm) | |
| Registration number (REACH) | 01-2119489379-17-XXXX |
| Index | 022-006-002 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 236-675-5 |
| CAS | 13463-67-7 |
| content % | <5 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Carc. 2, H351 (as inhalation) |

| | |
|---|---|
| Trimethoxyvinylsilane | |
| Registration number (REACH) | --- |
| Index | 014-049-00-0 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 220-449-8 |
| CAS | 2768-02-7 |
| content % | 1-<2,5 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Sens. 1B, H317 |

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Upon contact with stomach acid development of:

Methanol

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Skin irritation possible with prolonged contact.

Page 3 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 08.02.2022 / 0011
Replacing version dated / version: 01.11.2021 / 0010
Valid from: 08.02.2022
PDF print date: 08.02.2022
Seal-it® 315 Facade-LM

Allergic reaction possible.
Development of:
Methanol
The following applies to this substance:
Product results in a poisonous effect.
Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.
Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Ensure sufficient supply of air.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Or:

Pick up mechanically and dispose of according to Section 13.
Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid contact with eyes.
 Avoid long lasting or intensive contact with skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Store in a well ventilated place.
 Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The methanol listed below can arise upon contact with water.

| Chemical Name | Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m) | | Content %:<5 |
|---|--|-----|--------------|
| WEL-TWA: 10 mg/m ³ (total inhalable dust), 4 mg/m ³ (respirable dust) | WEL-STEL: --- | --- | |
| Monitoring procedures: | --- | | |
| BMGV: --- | Other information: --- | | |
| Chemical Name | Calcium carbonate | | Content %: |
| WEL-TWA: 4 mg/m ³ (respirable dust), 10 mg/m ³ (total inhalable dust) | WEL-STEL: --- | --- | |
| Monitoring procedures: | --- | | |
| BMGV: --- | Other information: --- | | |
| Chemical Name | Methanol | | Content %: |
| WEL-TWA: 200 ppm (266 mg/m ³) (WEL), 200 ppm (260 mg/m ³) (EU) | WEL-STEL: 250 ppm (333 mg/m ³) (WEL) | --- | |
| Monitoring procedures: | <ul style="list-style-type: none"> - Draeger - Alcohol 25/a Methanol (81 01 631) - Compur - KITA-119 SA (549 640) - Compur - KITA-119 U (549 657) - DFG Meth. Nr. 6 (D) (Lösungsmittelgemische 6), DFG (E) (Solvent mixtures 6) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 65-1 (2004) - NIOSH 2000 (METHANOL) - 1998 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016 - Draeger - Alcohol 100/a (CH 29 701) | | |
| BMGV: --- | Other information: Sk (WEL, EU) | | |

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m)

(GB)

Page 5 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.02.2022 / 0011

Replacing version dated / version: 01.11.2021 / 0010

Valid from: 08.02.2022

PDF print date: 08.02.2022

Seal-it® 315 Facade-LM

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|-----------------------------|------------|--------|-------------------|------|
| | Environment - freshwater | | PNEC | 0,184 | mg/l | |
| | Environment - marine | | PNEC | 0,0184 | mg/l | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 0,193 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 100 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 1000 | mg/kg dw | |
| | Environment - sediment, marine | | PNEC | 100 | mg/kg dw | |
| | Environment - soil | | PNEC | 100 | mg/kg dw | |
| | Environment - oral (animal feed) | | PNEC | 1667 | mg/kg feed | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 700 | mg/kg bw/d | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 10 | mg/m ³ | |

| Trimethoxyvinylsilane | | | | | | |
|-----------------------|--|------------------|------------|-------|------|---|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,4 | mg/l | Für entsprechendes Silantriol (Hydrolysp rodukt) ermittelt. |
| | Environment - marine | | PNEC | 0,04 | mg/l | Für entsprechendes Silantriol (Hydrolysp rodukt) ermittelt. |
| | Environment - water, sporadic (intermittent) release | | PNEC | 2,4 | mg/l | Für entsprechendes Silantriol (Hydrolysp rodukt) ermittelt. |
| | Environment - sewage treatment plant | | PNEC | 6,6 | mg/l | Für entsprechendes Silantriol (Hydrolysp rodukt) ermittelt. |

Page 6 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

| | | | | | | |
|---------------------|------------------------------------|------------------------------|------|------|-------------------|---|
| | Environment - sediment, freshwater | | PNEC | 1,5 | mg/kg dw | Für entsprechendes Silantriol (Hydrolyseprodukt) ermittelt. |
| | Environment - sediment, marine | | PNEC | 0,15 | mg/kg dw | Für entsprechendes Silantriol (Hydrolyseprodukt) ermittelt. |
| | Environment - soil | | PNEC | 0,06 | mg/kg dw | Für entsprechendes Silantriol (Hydrolyseprodukt) ermittelt. |
| Consumer | Human - dermal | Short term, systemic effects | DNEL | 0,1 | mg/kg bw/day | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 0,1 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 0,7 | mg/m ³ | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 0,1 | mg/kg bw/day | |
| Consumer | Human - inhalation | Short term, systemic effects | DNEL | 93,4 | mg/m ³ | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 0,2 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 2,6 | mg/m ³ | |
| Workers / employees | Human - inhalation | Short term, systemic effects | DNEL | 4,9 | mg/m ³ | |

| Calcium carbonate | | | | | | |
|--------------------------|--|------------------------------|------------|-------|-------------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - sewage treatment plant | | PNEC | 100 | mg/l | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 6,1 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 10 | mg/m ³ | |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 1,06 | mg/m ³ | |
| Consumer | Human - oral | Short term, systemic effects | DNEL | 6,1 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 4,26 | mg/m ³ | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 10 | mg/m ³ | |

| Methanol |
|-----------------|
|-----------------|

(GB)

Page 7 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|------------------------------|------------|-------|-----------------------|------|
| | Environment - freshwater | | PNEC | 154 | mg/l | |
| | Environment - marine | | PNEC | 15,4 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 570,4 | mg/kg | |
| | Environment - sediment, marine | | PNEC | 57,04 | mg/kg | |
| | Environment - soil | | PNEC | 23,5 | mg/kg | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 1540 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 100 | mg/l | |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 26 | mg/m ³ | |
| Consumer | Human - inhalation | Short term, local effects | DNEL | 26 | mg/m ³ | |
| Consumer | Human - dermal | Short term, systemic effects | DNEL | 4 | mg/kg body weight/day | |
| Consumer | Human - inhalation | Short term, systemic effects | DNEL | 26 | mg/m ³ | |
| Consumer | Human - oral | Short term, systemic effects | DNEL | 4 | mg/kg body weight/day | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 4 | mg/kg body weight/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 26 | mg/m ³ | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 4 | mg/kg body weight/day | |
| Workers / employees | Human - dermal | Short term, systemic effects | DNEL | 20 | mg/kg body weight/day | |
| Workers / employees | Human - inhalation | Short term, systemic effects | DNEL | 130 | mg/m ³ | |
| Workers / employees | Human - inhalation | Short term, local effects | DNEL | 130 | mg/m ³ | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 20 | mg/kg body weight/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 130 | mg/m ³ | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 130 | mg/m ³ | |

(GB) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Page 8 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 08.02.2022 / 0011
Replacing version dated / version: 01.11.2021 / 0010
Valid from: 08.02.2022
PDF print date: 08.02.2022
Seal-it® 315 Facade-LM

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. EN 14042.
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
With danger of contact with eyes.
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
Chemical resistant protective gloves (EN ISO 374).
If applicable
Rubber gloves (EN ISO 374).
Protective gloves made of butyl (EN ISO 374).
Protective nitrile gloves (EN ISO 374).
Minimum layer thickness in mm:
>= 0,4
Permeation time (penetration time) in minutes:
>= 480
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.
Protective hand cream recommended.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
Normally not necessary.

Thermal hazards:
Not applicable

Additional information on hand protection - No tests have been performed.
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

9.1 Information on basic physical and chemical properties

| | |
|---|--|
| Physical state: | Paste, solid. |
| Colour: | According to specification |
| Odour: | Slightly |
| Melting point/freezing point: | There is no information available on this parameter. |
| Boiling point or initial boiling point and boiling range: | There is no information available on this parameter. |
| Flammability: | There is no information available on this parameter. |
| Lower explosion limit: | Does not apply to solids. |
| Upper explosion limit: | Does not apply to solids. |
| Flash point: | Does not apply to solids. |
| Auto-ignition temperature: | Does not apply to solids. |
| Decomposition temperature: | There is no information available on this parameter. |
| pH: | Mixture is non-soluble (in water). |
| Kinematic viscosity: | There is no information available on this parameter. |
| Solubility: | Insoluble |
| Partition coefficient n-octanol/water (log value): | Does not apply to mixtures. |
| Vapour pressure: | There is no information available on this parameter. |
| Density and/or relative density: | 1,38 kg/l |
| Relative vapour density: | Does not apply to solids. |
| Particle characteristics: | There is no information available on this parameter. |

9.2 Other information

| | |
|-------------------|---------------------------|
| Explosives: | Product is not explosive. |
| Oxidizing solids: | No |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Strong heat
 Protect from humidity.
 Product may hydrolyse.

10.5 Incompatible materials

Avoid contact with strong alkalis.
 Avoid contact with strong acids.

10.6 Hazardous decomposition products

On contact with moist air:
 Methanol

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Seal-it® 315 Facade-LM

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|----------------------------------|----------|-------|---------|----------|-------------|---------------------------|
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | ATE | >20 | mg/l/4h | | | calculated value, Vapours |
| Skin corrosion/irritation: | | | | | | n.d.a. |

GB

Page 10 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

| | | | | | | |
|---|--|--|--|--|--|---|
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | No (skin contact), Analogous conclusion |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

| Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm) | | | | | | |
|---|----------|-------|---------|------------------------|--|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure) | |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | | |
| Acute toxicity, by inhalation: | LD50 | >6,8 | mg/l/4h | Rat | | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant, Mechanical irritation possible. |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | Not sensitising |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Mouse | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative |
| Germ cell mutagenicity: | | | | Mammalian | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | (Ames-Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Reproductive toxicity (Developmental toxicity): | | | | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | No indications of such an effect. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | Not irritant (respiratory tract). |

Page 11 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

| | | | | | | |
|---|-------|------|---------|-----|--|---|
| Symptoms: | | | | | | mucous membrane irritation, coughing, respiratory distress, drying of the skin. |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 3500 | mg/kg/d | Rat | | 90d |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 10 | mg/m3 | Rat | | 90d |

| Calcium carbonate | | | | | | |
|---|----------|-------|------------|----------|--|-----------------------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >2000 | mg/kg | Rat | OECD 420 (Acute Oral toxicity - Fixe Dose Procedure) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rat | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >3 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | No (skin contact) |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Carcinogenicity: | | | | | | No indications of such an effect. |
| Reproductive toxicity: | NOEL | 1000 | mg/kg bw/d | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development Tox. Screening Test) | |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | No indications of such an effect. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | No indications of such an effect. |
| Aspiration hazard: | | | | | | No |

Page 12 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

| | | | | | | |
|---|-------|-------|------------|-----|---|--|
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 1000 | mg/kg bw/d | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test) | |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 0,212 | mg/l | Rat | OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study) | |

| Methanol | | | | | | |
|---|-----------------|--------------|-------------|------------------------|--|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | ATE | 300 | mg/kg | Human being | | Experiences on persons. |
| Acute toxicity, by dermal route: | LD50 | 17100 | mg/kg | Rabbit | | Does not conform with EU classification. |
| Acute toxicity, by inhalation: | LC50 | 85 | mg/l/4h | Rat | | Not relevant for classification., Vapours |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Mouse | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative |
| Carcinogenicity: | | | | Mouse | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Negative |
| Reproductive toxicity: | NOAEL | 1,3 | mg/l | Mouse | OECD 416 (Two-generation Reproduction Toxicity Study) | |
| Specific target organ toxicity - repeated exposure (STOT-RE): | NOAEL | 0,13 | mg/l | Rat | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | |
| Symptoms: | | | | | | abdominal pain, vomiting, headaches, gastrointestinal disturbances, drowsiness, visual disturbances, watering eyes, nausea, mental confusion, intoxication, dizziness |

11.2. Information on other hazards

Page 13 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

| Seal-it® 315 Facade-LM | | | | | | |
|----------------------------------|----------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Endocrine disrupting properties: | | | | | | Does not apply to mixtures. |
| Other information: | | | | | | No other relevant information available on adverse effects on health. |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| Seal-it® 315 Facade-LM | | | | | | | |
|--|----------|------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Endocrine disrupting properties: | | | | | | | Does not apply to mixtures. |
| 12.7. Other adverse effects: | | | | | | | No information available on other adverse effects on the environment. |
| Other information: | | | | | | | DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a. |

| Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm) | | | | | | | |
|--|----------|------|--------|------|----------------------------------|--|--|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >100 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | LC50 | 48h | >100 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EC50 | 72h | 16 | mg/l | Pseudokirchnerie lla subcapitata | U.S. EPA-600/9-78-018 | |
| 12.2. Persistence and degradability: | | | | | | | Not relevant for inorganic substances. |
| 12.3. Bioaccumulative potential: | BCF | 42d | 9,6 | | | | Not to be expected |
| 12.3. Bioaccumulative potential: | BCF | 14d | 19-352 | | | | Oncorhynchus mykiss |

Page 14 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

| | | | | | | | |
|--|-----------|-----|--------|-------|-------------------------|--|-------------------------------------|
| 12.4. Mobility in soil: | | | | | | | Negative |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | | | >5000 | mg/l | Escherichia coli | | |
| Toxicity to bacteria: | LC0 | 24h | >10000 | mg/l | Pseudomonas fluorescens | | |
| Toxicity to annelids: | NOEC/NOEL | | >1000 | mg/kg | Eisenia foetida | | |
| Water solubility: | | | | | | | Insoluble20°C |

Calcium carbonate

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|-----------|------|-------|----------|-------------------------|--|--|
| 12.1. Toxicity to fish: | LC50 | 96h | | | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | No observation with saturated solution of test material. |
| 12.1. Toxicity to daphnia: | EC50 | 48h | | | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | No observation with saturated solution of test material. |
| 12.1. Toxicity to algae: | EC50 | 72h | >14 | mg/l | Desmodesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | 14 | mg/l | Desmodesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | | | | | | Not relevant for inorganic substances. |
| 12.3. Bioaccumulative potential: | | | | | | | Not to be expected |
| 12.4. Mobility in soil: | | | | | | | n.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC50 | 3h | >1000 | mg/l | activated sludge | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | |
| Toxicity to bacteria: | NOEC/NOEL | 3h | 1000 | mg/l | activated sludge | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | |
| Other organisms: | EC50 | 21d | >1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Glycine max |
| Other organisms: | EC50 | 21d | >1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Lycopersicon esculentum |

Page 15 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

| | | | | | | | |
|-------------------|-----------|-----|--------|----------|-----------------|---|-------------------------|
| Other organisms: | EC50 | 21d | >1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Avena sativa |
| Other organisms: | NOEC/NOEL | 21d | 1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Glycine max |
| Other organisms: | NOEC/NOEL | 21d | 1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Lycopersicon esculentum |
| Other organisms: | NOEC/NOEL | 21d | 1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Avena sativa |
| Other organisms: | EC50 | 14d | >1000 | mg/kg dw | Eisenia foetida | OECD 207 (Earthworm, Acute Toxicity Tests) | |
| Other organisms: | NOEC/NOEL | 14d | 1000 | mg/kg dw | Eisenia foetida | OECD 207 (Earthworm, Acute Toxicity Tests) | |
| Other organisms: | EC50 | 28d | >1000 | mg/kg dw | | OECD 216 (Soil Microorganisms - Nitrogen Transformation Test) | |
| Other organisms: | NOEC/NOEL | 28d | 1000 | mg/kg dw | | OECD 216 (Soil Microorganisms - Nitrogen Transformation Test) | |
| Water solubility: | | | 0,0166 | g/l | | OECD 105 (Water Solubility) | 20°C |

| Methanol | | | | | | | |
|--|----------|------|-------|------|---------------------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| 12.1. Toxicity to fish: | LC50 | 96h | 15400 | mg/l | Lepomis macrochirus | | EPA-660/3-75-009 |
| 12.1. Toxicity to daphnia: | EC50 | 96h | 18260 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EC50 | 96h | 22000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 99 | % | | OECD 301 D (Ready Biodegradability - Closed Bottle Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | BCF | | 28400 | | Chlorella vulgaris | | Not to be expected |

Page 16 of 19
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 08.02.2022 / 0011
 Replacing version dated / version: 01.11.2021 / 0010
 Valid from: 08.02.2022
 PDF print date: 08.02.2022
 Seal-it® 315 Facade-LM

| | | | | | | | |
|-----------------------|---------|----|-------|------|------------------|---|--|
| Toxicity to bacteria: | IC50 | 3h | >1000 | mg/l | activated sludge | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | |
| Other information: | Log Pow | | -0,77 | | | | |
| Other information: | DOC | | <70 | % | | | |
| Other information: | BOD | | >60 | % | | | |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

Hardened product:

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 08.02.2022 / 0011
Replacing version dated / version: 01.11.2021 / 0010
Valid from: 08.02.2022
PDF print date: 08.02.2022
Seal-it® 315 Facade-LM

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

General hygiene measures for the handling of chemicals are applicable.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2010/75/EU (VOC): ~ 0,1 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H351 Suspected of causing cancer by inhalation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

Carc. — Carcinogenicity

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

Skin Sens. — Skin sensitization

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

Page 18 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 08.02.2022 / 0011
Replacing version dated / version: 01.11.2021 / 0010
Valid from: 08.02.2022
PDF print date: 08.02.2022
Seal-it® 315 Facade-LM

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ASTM ASTM International (American Society for Testing and Materials)
ATE Acute Toxicity Estimate
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BSEF The International Bromine Council
bw body weight
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic

GB

Page 19 of 19
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 08.02.2022 / 0011
Replacing version dated / version: 01.11.2021 / 0010
Valid from: 08.02.2022
PDF print date: 08.02.2022
Seal-it® 315 Facade-LM

OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.