

Product

Seal-it® 450 PUR CLEANER is an effective and fast-acting cleaning product to remove/dissolve fresh/uncured PU foam stains and residues. Also suitable for cleaning and rinsing out PU guns.

Applications

- As a **gun cleaner**: Remove PU canister from gun, apply Seal-it® 450 PUR CLEANER, rinse gun out several times, let set well, then rinse out again. Remove Seal-it® 450 PUR CLEANER, clean/dry the threading of the gun adapter, then grease it with Vaseline, silicone and/or PTFE spray.
- As a **PU foam cleaner**: Put sprayer on valve, hold canister in correct spray direction and press sprayer in. Let Seal-it® 450 PUR CLEANER set for a bit, then thoroughly clean with a dry cloth or paper.

Properties

- Remove all fresh/uncured polyurethane foam residues.
- Fast-acting and effective, as long as the foam is fresh: cured foam must be removed mechanically.
- Excellently suited for thorough cleaning and rinsing of all PU gun types.
- Optimal spraying by hand with sprayer and excellent dosing with PU gun.
- Removes, degreases and cleans.
- Only suitable for surfaces and materials that are compatible with Seal-it® 450 PUR CLEANER.



Standard product line

Colour	12 x 500ml canister
N/A	SI-450-0000-500

Technical product data

Base	CLA
Propellant gas	(H)CFC-free

Shelf life

In unopened original packaging, stored in a cool dry place with canister upright, between +5°C and +25°C, the product will last up to 12 months after the production date.

Application conditions

- Shake Seal-it® 450 PUR CLEANER well before use.
- Hold Seal-it® 450 PUR CLEANER upright during use and point valve at the fresh foam residues. For proper spraying, keep an adequate distance, then activate by pressing the valve.
- If a gun is not working properly, put Seal-it® 450 PUR CLEANER on the gun adapter, spray through well several times, let set for approx.15 minutes, spray through well again and then remove canister.

Limitations & recommendations

Not suitable for solvent-sensitive surfaces. Use a suitable cover film to protect surrounding solvent-sensitive surfaces well from overspray. We recommend conducting a material compatibility test in advance on the surface to be treated, on a spot that is not visible.

Health & safety

Avoid long-term contact with skin. If uncured material gets in your eyes, rinse out thoroughly with plenty of water and consult a physician. We recommend wearing suitable safety goggles, gloves and work attire. Only use in well ventilated spaces and conditions. Do not smoke or use the product in the vicinity of an open flame. Store in a safe place out of the reach of children. The product safety data sheet is available on request.

Warranty & liability

Connect Products BV guarantees that its product will meet the specifications during its shelf life. Liability shall never exceed that stipulated in our terms and conditions of sale and supply. Under no circumstances shall the seller be held liable for any consequential damages. The information provided is the result of our testing and experience and is general in nature. However, it does not entail any liability. Users are responsible for performing their own tests to determine whether the product is suitable for the application.

