

Description

Seal-it® 510 CLEANER is a non-aggressive and effective cleaning product for degreasing various surfaces, specially developed to improve adhesion of glues, sealants, paints, coatings and lacquers.

Applications

- Specially developed to degrease and clean hard and smooth surfaces, such as glass, hard plastics, PCV, acrylic, metals, ceramics, aluminium, concrete, stone, composite and painted surfaces.
- As a primer for greasy surfaces on which sealant, adhesive and/or paint will be applied, to ensure a grease-free surface and optimal adhesion.
- As a degreaser and cleaning product to remove traces of grease and minor surface contamination from sealing joints to ensure a clean sealing joint, from an aesthetic and technical point of view. (paintability)
- Remove adhesive residues from stickers, straps, tape, film and spacers.
- Clean brushes and other tools.
- Remove oil, grease and lubricant residues.
- Remove rubber residues.
- Remove uncured sealant, adhesive, PU foam, paint, lacquer and stain.



Properties

- Significantly improves adhesion of sealants, adhesives and paint and lacquer systems (powder coatings).
- Thoroughly degreases and cleans non-porous surfaces.
- Fast-acting and effective.
- Easy to apply and wipe off.
- Low-odour, practically odourless.
- Highly evaporative and flammable.
- Do not leave traces or residues behind on the treated surface.
- UN-approved packaging.

Standard product line

Colour	10 x 1000ml can
Colourless	SI-510-000-1000

Other colours and/or packaging on request.

Technical product data

Base	SOLVENT	
Density	g/ml	0.85
Drying time	Min.	10
Flashpoint	°C	-14
Highly flammable	Yes	
Application temperature	°C	+5 to +40

Shelf life

In unopened original packaging, stored upright in a cool dry place, between +5°C and +25°C, the product will last up to 24 months after the production date.

Application conditions

- Application temperature (ambient and surface) between +5°C and +40°C.
- Use a clean cloth to apply Seal-it® 510 CLEANER evenly on the surface, then immediately use a clean lint-free cloth to wipe off the applied Seal-it® 510 Cleaner in the same direction until the surface is completely dry, after which the sealant, adhesive, paint, coating or lacquer can be applied.
- Extracts heat from the surface by evaporation, which cools it off. This may cause condensation on the treated surface. It is recommended to wait approx. 10 min. and then apply sealant or adhesive.

Limitations & recommendations

Only suitable for properly solvent-resistant surfaces. Limited suitability for acrylic surfaces. Conduct a material compatibility test first on the material and/or surface to be treated.

Health & safety

Avoid long-term contact with skin. If uncured material gets in your eyes, rinse out with plenty of water and consult a physician. Store Seal-it® 510 CLEANER in a closed container in a safe place outside of the reach of children. Highly evaporative and flammable. Use under good ventilation conditions. Do not smoke or use the product in the vicinity of an open flame. Wear safety goggles, gloves and suitable work attire. The product safety data sheet is available on request.

Warranty & liability

Connect Products BV guarantees that its product will meet the specifications during its shelf life. Liability shall never exceed that stipulated in our terms and conditions of sale and supply. Under no circumstances shall the seller be held liable for any consequential damages. The information provided is the result of our testing and experience and is general in nature. However, it does not entail any liability. Users are responsible for performing their own tests to determine whether the product is suitable for the application.

