

## Product

Seal-it® 515 ULTRA-WIPES are extremely convenient and effective cleaning wipes, specially designed for quick, easy and safe cleaning of hands, tools and many surfaces.

## Applications

- Removes uncured MS polymer, hybrid, silicone sealant, PU sealant, PU foam, most spray adhesives and other adhesives, epoxy materials, paints, lacquers, coatings, rubber cement and lubricants, such as greases and oils, from hands, tools and surfaces.

## Properties

- Versatile and extremely user-friendly.
- Dermatologist-tested.
- Highly effective.
- Cleans hands, tools and surfaces spotlessly in no time.
- Handy large packaging.



## Standard product line

Colour	6 cans of 100 units
White	SI-515-0000-100

## Technical product data

Wipe grammage	m <sup>2</sup>	26
Weight per pack	kg	3.9
Wipes per roll		100-150
Wipe length	mm	310
Wipe width	mm	280

## Ingredients

Aqua, alcohol denat, dimethyl glutarate, dimethyl adipate, dimethyl succinate, C9-11 parath-6, phenoxyethanol, methylparaben, propylparaben, 2-bromo-2-nitropropane-1,3-diol, glycerin, sodium, hydroxide.

## Shelf life

In unopened original packaging, stored in a cool dry place between +5°C and +25°C, the product will last up to 36 months after the production date.

### Application conditions

- Pull the first wipe, from the middle of the roll, through the opening in the centre of the lid.
- Then pull additional wipes as needed.
- If necessary, remove any residues with a moist cloth.
- For best results, clean the surface immediately after a spill.

### Health & safety

The product safety data sheet is available on request.

### Warranty & liability

Connect Products BV guarantees that its product will meet the specifications during its shelf life. Liability shall never exceed that stipulated in our terms and conditions of sale and supply. Under no circumstances shall the seller be held liable for any consequential damages. The information provided is the result of our testing and experience and is general in nature. However, it does not entail any liability. Users are responsible for performing their own tests to determine whether the product is suitable for the application.

